

METAL SOLUTIONS

EOS M 300-4 1kW

- ightarrow Reliable and repeatable quality
- ightarrow Up to 10 x higher productivity in Aluminium
- ightarrow Easily integrated in your production environment



EXPOSURE MODULE





4 precise 1kw lasers expose in a 300 x 300 mm square with each laser covering the entire area.



EOS M 300-4 1KW

TECHNICAL DATA

BUILD VOLUME	300 x 300 x 400* mm (11.8 x 11.8 x 15.7 in)
LASER TYPE	Yb-fiber laser; 4 x 1000 W
PRECISION OPTICS	4 F-theta-lens(es); 4 High-speed scanner(s)
SCAN SPEED	up to 7.0 m/s (23.0 ft/s)
FOCUS DIAMETER	approx. 100 μm (0.00394 in)
POWER SUPPLY	3 x 63 A
POWER CONSUMPTION	max. 19.6 kW / typical 16.0 kW
COMPRESSED AIR SUPPLY	7 Bar; 15 m³/h (102 psi; 530 ft³/h)

^{*} Height includes build plate

DIMENSIONS & WEIGHT



EOS M 300-4 1kW with Flex Dispenser

Height: 2,340 mm / Weight approx. 5,500 kg





EOS M 300-4 1kW

EOS Aluminium AlSi10Mg



EOS Copper CuCP



OPTIONAL ACCESSORIES





Manual and flexible powder handling



IPM M Setup Station M

Comfortable gas-tight unpacking from two sides and under inert gas

HEADQUARTERS

EOS GmbH Electro Optical Systems Robert-Stirling-Ring 1 82152 Krailling / Munich Germany Tel.: +49 89 893 36-0 Email: info@eos.info URL: www.eos.info

Status as of 23.08.2024. Subject to technical modifications. EOS is certified according to ISO 9001. FOS®. Additive Minds® Alumide®. AMO®. CarbonMide®. DirectMetal®. DMLS®. FOSAME®. FOSI

EOS®, Additive Minds® Alumide®, AMQ®, CarbonMide®, DirectMetal®, DMLS®, EOSAME®, EOSINT®, EOSIZE®, EOSPACE®, EOSPRINT®, EOSTATE®, EOSTYLE®, FORMIGA®, LaserProFusion®, PA 2200®, PrimeCast® and PrimePart® are registered trademarks of EOS GmbH Electro Optical Systems in some countries. For more information visit www.eos.info/trademarks.